



SECURICAM Network™

DCS-6620G 10x Optical Zoom Internet Camera



D-Link, a leading provider of wired and wireless IP Cameras, introduces a new member of the SECURICAM Network family of Internet Cameras: the DCS-6620G 10x Optical Zoom Internet-Camera. Featuring dual codec support, a 10x optical zoom lens, 802.11g wireless connectivity, built-in microphone, and low-light sensitivity, the DCS-6620G is the ultimate remote monitoring solution for your security needs.

The DCS-6620G features motorized pan, tilt, and optical/digital zoom, giving you greater remote viewing options. With a 10x optical zoom auto focus/auto iris lens, get greater clarity from your recordings than digital zoom alone. The 10x optical zoom lens delivers the level of detail necessary to identify people, license plate numbers, and other important details that are difficult to clearly view with digital zoom.

With support for both Motion JPEG and MPEG-4 recording, the DCS-6620G is well suited for various recording scenarios. Motion JPEG delivers greater file integrity, making it ideal for critical monitoring situations. MPEG-4 video has smaller file sizes, making it more useful for extended recording periods or for use in low bandwidth networks.

The DCS-6620G also utilizes D-Link's 2-Way Audio feature with its built-in microphone. Attach a speaker to the DCS-6620G and remotely communicate with subjects near the camera. An ideal location to use the 2-Way Audio feature includes point-of-entry areas, where you might want to identify a person before granting access.

With the ability to record video in low light settings, the DCS-6620G can provide exceptional nighttime surveillance. Extreme low light sensitivity of .05 Lux enables recording in near total darkness.

You can remotely monitor your camera using a web-based interface, or through D-Link's IP surveillance software. The web-based interface lets up to 10 simultaneous users to view the live feed from the camera. Using the feature-rich IP surveillance program, monitor and manage up to 16 cameras, set recording schedules, configure motion detection settings, and change settings to multiple cameras.

Featuring 802.11g wireless connectivity, the DCS-6620G offers greater installation flexibility. Using the freedom of wireless connectivity, install your DCS-6620G in locations without the hassle of running Ethernet cables. The DCS-6620G supports WPA-PSK, TKIP, and WEP for establishing secure connections to your wireless network.

Enjoy greater peace of mind with high quality security solutions from the SECURICAM Network series of Internet Cameras. The DCS-6620G offers maximum versatility for all monitoring situations, making it the smart investment for your security needs.

Features:

Motorized Pan/Tilt/Zoom

- 1x - 10x Optical Zoom
- 2x, 4x, 6x, 8x, 10x Digital Zoom
- Pan 270° ± 135°
- Tilt: 90° ± 45°

User-Selectable Compression Codec

- MJPEG
- MPEG-4

Multiple Connectivity Options

- 802.11g Wireless
- 10/100 Ethernet

2-Way Audio Support

- Built-in Microphone
- 2.5mm A/V Out

Extreme Low Light Sensitivity

- .05 Lux / F1.8 (Low Lux)
- 1.5 Lux / F1.8 (Typical)

Smooth Video Recording

- Up to 30fps at 352x240
- Up to 10fps at 704x480

DCS-6620G

10x Optical Zoom Internet Camera

Technical Specifications

Software

Modes of Operation

- MJPEG
- MPEG-4

Security

- 14-Digit Password
- 20 User Accounts
- 10 Simultaneous Users

Network Protocols

- TCP/IP
- 802.3
- 802.3u
- DDNS
- UPnP
- NTP
- SMTP
- FTP
- HTTP

Wireless Security

- WPA-PSK
- TKIP
- 128-bit WEP Encryption

Camera

Video Resolution

- Up to 30fps at 352x240
- Up to 10fps at 704x480

Physical & Environmental

Device Ports

- 10/100Mbps Fast Ethernet
- Power
- External Mic
- A/V Out

Diagnostic LEDs

- 2 LEDs for POST, Connection, and Heartbeat

Power Input

- External Power Supply
- 12V DC 1.5A

Power Consumption

- 5.5W (Still)
- 8.0W (Moving)

Dimensions

- 4.06" (L) x 4.07" (W) x 4.35" (H)

Weight

- 14.4 oz.

Temperature

- Operating: 32° F - 140° F
- Storage: 22° F - 167° F

Humidity (non-condensing)

- 5% to 95%

Emission (EMI)

- FCC class B
- CE class B

Safety

- LVD (EN 60950)

Warranty

- 1-Year

